



# 1 Gallon (4 Liter) Benchtop Solvent Recycler

- Description:** Recycles xylene, xylene substitutes, alcohol and acetone with 90-95% recovery.
- Model Number:** MSLV-99-U-4-A (120 V configuration)  
MSLV-99-CE-4-A (220/240 V configuration)
- Dimensions:** 14.5 inches wide, 32.75 inches high, 15.75 inches deep  
(37 cm wide, 83 cm high, 40 cm deep)
- Electrical Configurations:** 120 VAC, 6.0 A, 50/60 Hz  
220 VAC, 3.0 A, 50/60 Hz  
240 VAC, 3.3 A, 50/60 Hz
- Cycle Times:** Xylene: 2 to 3 hours per gallon  
(30 to 45 minutes per liter)  
Ethanol: 3 to 4 hours per gallon  
(45 to 60 minutes per liter)



## Specifications:

- Fractional distillation
- Microprocessor controlled, fully automated
- Automatic waste disposal
- No cool-down between runs
- Built-in spill containment
- Satisfies the latest Uniform Fire Code requirements for solvent distillation units
- No water hook-up or special ventilation required
- No hot surfaces – cool to the touch
- [ETL Listed to UL 61010 and UL 2208](#) and comparable Canadian standards (CSA) for 120 V configuration
- Built to CE Standards