



2.5 Gallon (10 Liter) Benchtop Supreme Solvent Recycler

- Description:** Recycles xylene, xylene substitutes, alcohol and acetone with 90-95% recovery
- Model Number:** MSLV-03-U-10-A (120 V configuration)
MSLV-03-CE-10-A (220/240 V configuration)
- Dimensions:** 13 inches wide, 39 inches high, 23 inches deep
(33 cm wide, 99 cm high, 59 cm deep)
- Electrical Configurations:** 120 VAC, 15.0 A, 50/60 Hz
220 VAC, 7.5 A, 50/60 Hz
240 VAC, 8.2 A, 50/60 Hz
- Cycle Times:** Xylene: 60 to 75 minutes per gallon
(15 to 20 minutes per liter)
Ethanol: 90 to 115 minutes per gallon
(20 to 30 minutes per liter)



Specifications:

- Fractional distillation
- Microprocessor controlled, fully automated
- Automatic waste disposal
- No cool-down between runs
- Built-in spill containment
- Satisfies the latest Uniform Fire Code requirements for solvent distillation units
- No water hook-up or special ventilation required
- No hot surfaces – cool to the touch
- ETL Listed to UL 61010 and UL 2208 and comparable Canadian standards (CSA) for 120 V configuration
- Built to CE Standards

Alternate Configuration: 2.5 Gallon Benchtop Compact Solvent Recycler (available in North America only)

Model Number: MSLV-03-U-10 (120 V configuration)

- Manual waste disposal
- All other specifications remain the same