



5 Gallon (20 Liter) FormaSolve Recycler Combination Solvent and Formalin Cart-Mounted Recycler

- Description:** Recycles xylene, xylene substitutes, alcohol and acetone with 90-95% recovery and formalin and alcoholic formalin with 80% recovery.
- Model Number:** FormaSolve-99-U-20 (120 V configuration)
FormaSolve-99-CE-20 (220/240 V configuration)
- Dimensions:** 24.25 inches wide, 67 inches high, 30.5 inches deep
(62 cm wide, 170 cm high, 77 cm deep)
Plus shroud on side: 4 inches (10 cm)
- Electrical Configurations:** 120 VAC, 15.0 A, 50/60 Hz
220 VAC, 7.5 A, 50/60 Hz
240 VAC, 8.2 A, 50/60 Hz
- Cycle Times:** Xylene: 60 to 75 minutes per gallon
(15 to 20 minutes per liter)
Ethanol: 90 to 115 minutes per gallon
(20 to 30 minutes per liter)
Formalin: Approximately 120 minutes per gallon
(30 minutes per liter)



Specifications:

- Fractional distillation for solvent recycling; simple distillation for formalin recycling
- Microprocessor controlled, fully automated
- Automatic waste disposal
- No cool-down between runs
- Built-in spill containment
- Satisfies the latest Uniform Fire Code requirements for solvent distillation units
- No water hook-up or special ventilation required
- No hot surfaces – cool to the touch
- Mobile
- Electric fill pump
- [ETL Listed to UL 61010 and UL 2208](#) and comparable Canadian standards (CSA) for 120 V configuration
- Built to CE Standards

**Alternate Configuration: 2.5 Gallon FormaSolve Recycler
(available in North America only)**

Model Number: FormaSolve-99-U-10 (120 V configuration)