



Cart-Mounted Formalin Recycler

Description: Recycles formalin and alcoholic formalin with 80% recovery.

Model Number: **5 Gallon (20 Liter) Recycler**
FMA-99-U-20 (120 V configuration)
FMA-99-CE-20 (220/240 V configuration)

10 Gallon (40 Liter) Recycler
FMA-99-U-40 (120 V configuration)
FMA-99-CE-40 (220/240 V configuration)

Dimensions: **5 Gallon (20 Liter) Recycler**
24.25 inches wide, 67 inches high, 30.5 inches deep
(62 cm wide, 170 cm high, 77 cm deep)

10 Gallon (40 Liter) Recycler
24.25 inches wide, 67 inches high, 30.5 inches deep
(62 cm wide, 170 cm high, 77 cm deep)
Plus shroud on side: 4 inches (10 cm)

Electrical Configurations: 120 VAC, 15.0 A, 50/60 Hz
220 VAC, 7.5 A, 50/60 Hz
240 VAC, 8.2 A, 50/60 Hz

Cycle Times: Approximately 120 minutes per gallon
(30 minutes per liter)

Specifications:

- Recycling through distillation
- Microprocessor controlled, fully automated
- Automatic waste disposal
- No cool-down between runs
- Built-in spill containment
- No water hook-up or special ventilation required
- No hot surfaces – cool to the touch
- Mobile
- Electric fill pump
- [ETL Listed to UL 61010 and UL 2208](#) and comparable Canadian standards (CSA) for 120 V configuration
- Built to CE Standards

Alternate Configuration: 2.5 Gallon Cart-Mounted Formalin Recycler
(available in North America only)

Model Number: FMA-99-U-10 (120 V configuration)

