



## TechnoClean F-2500 25 Gallon Solvent Recycler

**Description:** Uses fractional distillation to reclaim high purity solvents for reuse. Suitable for multiple solvent waste streams, high purity solvent recovery and/or customized applications.

**Dimensions:** 58 inches long, 34 inches wide, 88 inches high  
**(on 15 inch legs)** (147 cm long, 86 cm wide, 224 cm high)

**Electrical** 220/240 VAC, 3 Ø  
**Configurations:** 440/480 VAC, 3 Ø

### Specifications:

- [ETL Listed to UL 61010 and UL 2208](#) and comparable Canadian standards (CSA) for operation in a non-hazardous environment
- Recycling through fractional distillation
- Purity of recycled solvents up to 99.9%
- Microprocessor-controlled with easy-to-read LCD display
- User-friendly – virtually automatic operation
- Custom programming for special solvent requirements or additional solvents
- All metal design, with dual wall 304 stainless steel tank
- Waste removal versatility – both drain and bag capabilities
- Disposable bag liners available (Pack of 25 bag liners included with recycler purchase)
- Thermal-oil heating: temperature range from 65°C to 210°C
- Heater wattage – 9,200 W at 240/480 V
- Air-cooled; no water hook-up or special ventilation required
- Multiple redundant safety features with auto shut-offs – meets OSHA requirements
- Phone installation and training included
- Designed and manufactured in the USA by CBG Technologies
- Customer service telephone support available

### Options:

- May be built to Class 1 Division 1 standard
- Fill pump
- Auto-fill and continuous processing options
- Vacuum feature (to recycle high boiling waste solvents)
- Chiller (to condense low boiling recycled solvents)
- Shorter or Longer Legs
- On-site training
- Extended warranties and annual maintenance contracts available

